

## DIESEL FORKLIFT (1.5-3.5 TON)



## SPECIFICATIONS

	FD 18 C	FD 25 C	FD 30 C	FD 35 C
Model designation	FD 18 C	FD 25 C	FD 30 C	FD 35 C
Power Unit	Diesel	Diesel	Diesel	Diesel
Loading capacity	1800 kg	2500 kg	3000 kg	3500 kg
Load center	500 mm	500 mm	500 mm	500 mm
Total weight	2910 kg	3800 kg	4450 kg	4550 kg
Tire size (front)	6.50-10-10PR	7.00-12-12PR	28*9-15-12PR	28*9-15-12PR
Tire size (rear)	5.00-8-8PR	6.50-9-10PR	6.50-10-10PR	6.50-10-10PR
Wheels, number front/rear	2/2	2/2	2/2	2/2
Length of fork face	2270 mm	2565 mm	2680 mm	2720 mm
Overall width	1075 mm	1150 mm	1225 mm	1225 mm
Lifting height	3000-5000 mm	3000-6000 mm	3000-6000 mm	3000-6000 mm
Ground clearance	100 mm	110 mm	110 mm	110 mm
Min. turning radius	2100 mm	2250 mm	2300 mm	2340 mm
Travel speed, with/without load	0-20 km/h	0-20 km/h	0-20 km/h	0-20 km/h
Lifting speed, with/without load	590/650	600/550	490/510	490/510
Climbing ability	23%	23%	23%	23%
Service brake	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Fuel tank capacity	35 L	55 L	55 L	80 L
Working pressure	14-15.5 mpa	14-17 mpa	14-17 mpa	15-18 mpa