

## FS45 SKID STEER LOADER



### STANDARD MACHINE

Deluxe enclosed operator cabin  
Preheat starting assist system for extreme cold weather  
Auxiliary hydraulic couplers  
Hydraulic joystick controls  
Standard bucket

### OPTIONAL EXTRAS FOR MACHINE

- Air conditioner (Cabin fitted with a heater as standard)
- Speed transmission system

Attachments: Breaker, Angle blade, Auger, Sweeper, Pallet fork, Combination bucket, Mower, Asphalt cutter.

## SPECIFICATIONS

Maker/Model	XINCHAI (498)	Width with bucket (mm)	1750
Net power	45KW/2450rpm	Track width (mm)	1450
Type	4 Cylinder in-line, Water cooled, 4 stroke, Diesel engine	Wheelbase (mm)	991
Displacement (L)	3.168	Ground clearance (mm)	190
Rated operating capacity (kg)	800	Dump angle	40°
Tipping load (kg)	1400	Dumping height (mm)	2300
Bucket capacity (m3)	0.50	Maximum Reach (mm)	710
Operating weight (kg)	2650	Rollback at ground	26°
Max. travel speed (km/h)	11.8	Angle of departure	20°
Hydraulic pump flow (L/min)	62.5	Pump	Germany Rexroth
Fuel/Hyd oil tank capacity (L)	50/50	Motor	Italy BONDIOLI
Tires	10/16.5NHS	Gear pump/Cylinder	Italy BONDIOLI
Overall dimensions (mm)	2950x1750x2060	Multi Valve/Pilot valve	Italy BONDIOLI
Height at maximum extension (mm)	3680	Adjust balance valve	USA SAUER
Height to bucket hinge pin (mm)	2950	Quick hitch	Italy DNP